

GNC-140

GaN Wall Charger 140W

2x USB-C PD 140W, 1x USB-C PD 20W, 1x USB-A QC 3.0



Max output power



Charge up to 4 devices



Multi-plug included



Eco friendly packaging

Charge fast, charge more

Verbatim's 140W GaN Wall Charger combines two USB-C PD 140W ports, one USB-C PD 20W port and one USB-A 18W QC 3.0 port in a sleek, palm sized design. Ideal for the office, home or travelling to power your laptop, tablet, smartphone, gaming devices, and more. With its foldable US prongs and replaceable EU and UK plugs, it's the ultimate travel companion.

Gallium Nitride (GaN) technology delivers high-powered, fast, efficient charging, generates less heat and allow to have smaller and lighter chargers, making them ultra-portable and ideal for travel.

The GNC-140 charger is made with high-quality, flame-resistant materials and features four safety protection systems to ensure your safety while charging.

GNC-140

GaN Wall Charger 140W

2x USB-C PD 140W, 1x USB-C PD 20W, 1x USB-A QC 3.0

General Information				
Material	PC fireproof			
Colour	Black/Grey			
Input Plug Formats	US (Type A) / EU (Type C) / UK (Type G)			
Supported devices	Laptop, iPhone, iPad, Smartphones, Tablet PCs, MP3/MP4 players, smartwatch, etc.			
Power				
Input	100-240 V AC 50/60Hz 2.1A (Max)			
Total Output	140W Max			
Single Port Output				
USB-C1 PD 3.1	3.3-21V=5A, 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=5A, 28V=5A (140W Max)			
USB-C2 PD 3.1	3.3-21V=5A, 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=5A, 28V=5A (140W Max)			
USB-C3 PD 3.0	5V=3A, 9V=2.22A, 12V=1.67A (20W Max)			
USB-A QC 3.0	5V=3A, 9V=2A, 12V=1.5A (18W Max)			
Multiport Output	USB-C1 PD 3.1	USB-C2 PD 3.1	USB-C3 PD 3.0	USB-A QC 3.0
USB-C1+USB-C2	65W	65W	-	-
USB-C1+USB-C3	100W	-	20W	-
USB-C1+USB-A	100W	-	-	18W
USB-C2+USB-C3	-	100W	20W	-
USB-C2+USB-A	-	100W	-	18W
USB-C3+USB-A	-	-	15W shared	
USB-C1+USB-C2+USB-C3	65W	45W	20W	-
USB-C1+USB-C2+USB-A	65W	45W	-	18W
USB-C1+USB-C3+USB-A	100W	-	15W shared	
USB-C2+USB-C3+USB-A	-	100W	20W shared	
USB-C1+USB-C2+USB-C3+USB-A	65W	45W	15W shared	



USB-C 1/2 PD 3.1 (PPS) Output:

Max PD 140W (when used alone)

USB-C3 PD 3.0 Output:

Max PD 3.0 20W (when used alone)

USB-A QC 3.0 Output:

Max 18W (when used alone)



EU
Type C



UK
Type G



US
Type A

GNC-140

GaN Wall Charger 140W

2x USB-C PD 140W, 1x USB-C PD 20W, 1x USB-A QC 3.0



Other Features	
Compliance	EN 55032:2015+A11:2020+A1:2020 EN 55035:2017+A11:2020 EN IEC 61000-3-2:2019+A1:2020 EN 61000-3-3:2013+A1:2019+A2:2021 EN IEC 62368-1:2020+A11:2020
ROHS compliance	Yes
Output short circuit protect	On short circuit protection situation, will stop charging to protect devices
Over-voltage protection	Yes
Over-current protection	Yes
Over-temperature protection	Yes

PN	Description	Bar Code	EAN128 Code	EAN14 Code
32203	Verbatim GNC-140 GaN Charger 140W with 2 x USB-C® PD 140W / 1 x USB-C® PD 20W / 1 x USB-A QC 3.0 (EU/UK/US)	023942322030	(02)00023942322030(37)10(91)892 (02)00023942322030(37)20(91)892	20023942322034 50023942322035

Logistic Information	
Product Dimensions L x W x H	76.5 x 31.3 x 67.7mm
Product Weight	270 grams
Units per Pack	1
Pack Dimensions L x W x H	110 x 47 x 131.5mm
Pack Weight	390 grams (approx)
Units per Inner Carton	10
Inner Carton Dimensions L x W x H	285 x 255 x 131mm
Inner Carton Weight	4 100 grams
Units per Outer Carton	20
Outer Carton Dimensions L x W x H	305 x 280 x 302mm
Master Cartons Weight	8 600
Master Cartons per Layer	9
Layers per Pallet	3
Units per Pallet	540



GNC-140

GaN Wall Charger 140W

2x USB-C PD 140W, 1x USB-C PD 20W, 1x USB-A QC 3.0



Front



Angled



EU Plug



UK Plug



US Plug



Pack content



Packaging flat



Packaging 3D

Pack Contents:

- GaN Wall Charger
- EU adapter
- UK adapter
- Quick Start Guide

Warning

- INDOOR USE ONLY