

Business & Productivity Monitor

Der PRO MP341CQPHGN E12 ist der beste 21:9 UWQHD Curved Monitor für Multitasking. Seine ultra-breite Bildschirmgröße ermöglicht es den Benutzern, immer alles im Blick zu haben. Der 1500R gebogene Bildschirm und die 120Hz Flicker-Free-Technologie tragen zu einem optimalen Seherlebnis bei.



SELLING POINTS

- 21:9 UWQHD-34"-Bildschirm verbessert Multitasking und erweitert Ihren Horizont.
- Die 1500R-Krümmung sorgt für ein besonders immersives Seherlebnis bei der Arbeit und im Alltag.
- Type-C 98 W Stromversorgung sowie Display- und KVM-Switch.
- Genießen Sie hochwertige Unterhaltung mit einer flüssigen Bildwiederholrate von 120 Hz.
- Das TÜV-zertifizierte Display schont Ihre Augen.
- Die MSI EyesErgo-Technik mit Anti-Flicker-Technik hilft, Augenbelastungen und Ermüdungserscheinungen vorzubeugen.
- MSI Eye-Q Check hilft dir dabei, deine Augen selbst zu überprüfen und erinnert dich daran, bei längerer Nutzung des Monitors Pausen einzulegen.
- Genieße eine aufgeräumte Umgebung dank praktischem und abnehmbarem Kabelmanagement und Standard-Vesa Design.
- MSI Power Link ermöglicht das Einschalten Ihres MSI-Desktops mit einem einzigen Druck auf den Netzschalter des Monitors.
- Mit mehreren Eingangsquellen wie HDMI™ - und DP-Anschlüssen sind Sie für alles gerüstet, was Sie brauchen
- Zwei eingebaute Lautsprecher.



1. 5 Wege Joysticknavigation
2. Stromanschluss
3. Kopfhöreranschluss
4. 1x HDMI™ 2.0b (UWQHD@100Hz)
5. 1x DisplayPort 1.4a
6. Typ-C (DP alt.) mit 98W PD
7. 1x USB 5Gbps Typ-B
8. 4x USB 5Gbps Typ-A
9. Kensington Lock

SPECIFICATION

Model	Part No	PROMP341CQPHGNE12
	Color	ID1/Black-Black
Display	Screen Size	34" (86.36 cm)
	Active Display Area (mm)	797.22(H) x 333.72(V)
	Curvature	Curve 1500R
	Panel Type	VA
	Resolution	3440x1440 (UWQHD)
	Pixel pitch (mm)	0.23175(H)x0.23175(V)
	Aspect Ratio	21:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~120Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	3500:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	70.6~176.4 KHz(H) / 48~120 Hz(V)
	Refresh Rate	120Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	100%/86%
	NTSC (CIE1931 area percentage/overlap)	86%/80%
	sRGB (CIE1976 area percentage/overlap)	114%/98%
	sRGB (CIE1931 area percentage/overlap)	121%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	98%/89%
	Adobe RGB (CIE1931 area percentage/overlap)	90%/84%
	DCI-P3 (CIE1976 area percentage/overlap)	91%/91%
	DCI-P3 (CIE1931 area percentage/overlap)	90%/90%
	Rec.709 (CIE1976 area percentage/overlap)	114%/98%
	Rec.709 (CIE1931 area percentage/overlap)	121%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	66%/66%
	Rec.2020 (CIE1931 area percentage/overlap)	64%/64%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
Schnittstellen	USB Type C (DisplayPort Alternate)	1
	Headphone-out	1
	USB 3.2 Gen 1 Type A	4
	USB 3.2 Gen 1 Type B	1
	Lock type	Kensington Lock
	Speaker	2Wx 2
	HDMI	1
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a (HBR3)
	DisplayPort HDCP version	2.3
Garantie	Warranty	36 Monate Pick-Up & Return
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	SDR : 25 / HDR : 50
	Annual Energy Consumption (KWh)	44
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E (SDR) G (HDR)
	Power Cord Type	C13

Zubehör	DisplayPort Cable	1
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	1
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	1
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-45° ~ 45°
	Adjustment (Height)	0 ~ 150 mm
	Adjustment (Pivot)	-10° ~ 10°
	VESA Mounting	100x100mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	809.3 x 234.9 x 549.7
	Product Dimension without Stand (WxDxH) (mm)	809.3 x 112.8 x 365.8
	Stand Dimension (WxDxH) (mm)	300 x 234.9 x 411.5
	Weight (Net kg)	9.
	Weight Without Stand (kg)	6.2
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	98.5 x 17.1 x 51.3
	Outer Carton Dimension (WxDxH) (cm)	100 x 18.6 x 53.6
	Weight (Gross kg)	12.3
Barcode Info	EAN	4711377421928