

PATH TO THE FUTURE

PRO MAXP 271QPX14G: Ein 27 Zoll 144Hz QD-OLED-Monitor. Ausgestattet mit gleichmäßiger Helligkeit für eine konstante Helligkeit in SDR und HDR. Er liefert präzise, lebendige Farben und schützt die Augen durch die VisiClarity-Technologie und Farbsynchronisation.



SELLING POINTS

- MSI QD-OLED Panel – mit beeindruckender Bildqualität und schneller Reaktionszeit.
- Uniform Luminance – HDR-Kurvenanpassung, mit der du die HDR-Kurve individuell einstellen kannst und ein gleichmäßig flüssiges HDR-Erlebnis genießt.
- HDR-Technik erzeugt Bilder mit mehr Details.
- MSI OLED Care 2.0 – reduziert das Risiko von OLED-Bildeinbrennen.
- Stellt sicher, dass die Farben dem Marktstandard entsprechen – Delta E ≤ 2.
- 3 Jahre Schutz gegen Burn-in – inklusive OLED-Burn-in Abdeckung.
- TÜV-zertifiziertes Display sorgt für Schutz und Gesundheit der Augen.
- MSI EyesErgo Technik mit Anti-Flicker hilft, Augenbelastung und Ermüdung zu reduzieren.



1. Kopfhörerausgang
2. 2x HDMI™ 2.0b (WQHD@144Hz)
3. 1x DisplayPort 1.4a
4. 1x Typ-C (DP alt.) mit 15W PD
5. Kensington Lock
6. Stromanschluss

SPECIFICATION

Model	SKU Number	PROMAX271QPX14G
	Entity MKT Name	PRO MAX 271QPX14G
	Part No	PROMAX271QPX14G
	Color	ID1/Black-Black
Display	Screen Size	27" (69 cm)
	Active Display Area (mm)	590.42(H) x 333.72(V)
	Curvature	Flat
	Panel Type	QD-OLED
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2292(H)x0.2292(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~144Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	200
	HDR Brightness (Peak nits)	400
	Contrast Ratio	1500000:1
	Signal Frequency	TBD
	Refresh Rate	144HZ
	Response Time (GTG)	0.03ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	120.67%/94.41%
	NTSC (CIE1931 area percentage/overlap)	104.57%/92.43%
	sRGB (CIE1976 area percentage/overlap)	138.39%/100%
	sRGB (CIE1931 area percentage/overlap)	147.64%/100%
	Adobe RGB (CIE1976 area percentage/overlap)	118.62%/98%
	Adobe RGB (CIE1931 area percentage/overlap)	109.44%/94.87%
	DCI-P3 (CIE1976 area percentage/overlap)	110.2%/99.07%
	DCI-P3 (CIE1931 area percentage/overlap)	108.83%/98.47%
	Rec.709 (CIE1976 area percentage/overlap)	138.39%/100%
	Rec.709 (CIE1931 area percentage/overlap)	147.64%/100%
	Rec.2020 (CIE1976 area percentage/overlap)	80.3%/80.3%
	Rec.2020 (CIE1931 area percentage/overlap)	78.08%/78.08%
	Surface Treatment	Anti-Glare Low Reflection
	Display Colors	1.07B
	Color bit	10 bits
Schnittstellen	USB Type C (DisplayPort Alternate)	1
	Headphone-out	1
	Lock type	Kensington Lock
	Speaker	2.5Wx 2
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a (HBR3)
	DisplayPort HDCP version	2.3
Garantie	Warranty	36 Monate Pick-Up & Return
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	TBD
	Annual Energy Consumption (KWh)	TBD
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	TBD
	Power Cord Type	C13



BUSINESS PRODUCTIVITY MONITOR

PRO MAX 271QPX14G

PRO MAX 271QPX14G

Zubehör	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-30° ~ 30°
	Adjustment (Height)	0 ~ 150 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	100x100mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	N/A
	Product Dimension without Stand (WxDxH) (mm)	N/A
	Stand Dimension (WxDxH) (mm)	N/A
	Weight (Net kg)	N/A
	Weight Without Stand (kg)	N/A
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	N/A
	Outer Carton Dimension (WxDxH) (cm)	N/A
	Weight (Gross kg)	N/A
Barcode Info	EAN	4711377430005